

LXinstruments GmbH
Rudolf-Diesel-Str. 36
71154 Nufringen
Germany



TECHNICAL PRODUCT INFORMATION

Test & measurement instruments

- high - quality
- moderate prices
- excellent precision

Your contact:

Technical support, services, demo & rental equipment, price information
& quotes, consulting:

Tel.: +49(0)7032 / 895 93-3

Mail: sales@lxinstruments.com

Web: www.lxinstruments.com

Shop: www.lxinstruments.com/shop

EX1402



FEATURES

- 16-channel Isolated voltage Measurements
- 24-bit SAR ADC per Channel
- 128k samples/second/channel Sample Rate
- 500V channel-ground isolation
- 1000V channel-channel isolation
- Input voltage ranges peak: $\pm 420\text{V}/\pm 10\text{V}/\pm 1\text{V}$
- Data logger acquisition mode
- 3-Pin screw terminal Input Connector
- LXI Ethernet Interface
- IEEE-1588 Synchronization
- Power over Ethernet (PoE+) or 12– 50 V DC input
- Simultaneous Data Streaming
- 8-bit bank isolated digital I/O
- Full-featured Embedded Web Interface
- Compact 1U Half-rack Form Factor

16-CHANNEL ISOLATED HIGH VOLTAGE MEASUREMENT INSTRUMENT

APPLICATIONS

BATTERY AND FUEL CELL TEST

DATA ACQUISITION

GAS TURBINE TEST

HALT/HASS

HEALTH MONITORING

This and the technical data disclosed are proprietary to VTI Instruments and shall not, without express written permission of VTI Instruments, be used, released, or disclosed in whole or part or used to solicit quotations from a competitive source or be used for manufacture by anyone other than VTI Instruments. The information here has been developed at private expense and may only be used for purposes of engineering evaluation and for incorporation into technical documents which specify procurement from VTI Instruments.

EX1402 16-CHANNEL ISOLATED HIGH VOLTAGE MEASUREMENT INSTRUMENT



EX1402 Precision, Isolated High Voltage Measurements

The AMETEK VTI Instruments EX1402 adds isolation and high-speed measurement capability to the popular EX1400 Series of instruments, an advanced, full-featured data acquisition family designed to acquire precision data from voltage sensors. The EX1402 delivers accurate and highly repeatable voltage measurements by implementing fully integrated signal conditioning, 24-bit ADC's, on a per-channel basis. With industry-leading sample rates of 128 kSa/s/channel, the EX1402 is well-suited for a wide range of applications that require maximum accuracy, flexible sampling rates, and protection against damaging voltage levels. Enhanced power options, including AC, DC, and PoE+, adapt to virtually any application requirement while the stand-alone data logging and parallel data streaming capabilities break new ground for performance and flexibility.

Scalable for High-Speed Synchronized Data Acquisition

In addition to the core set of features, the EX1402 integrates Extended Functions as defined in the LXI specifications to provide box-to-box synchronization to precisely correlate acquired data as well as timestamping of data and LAN Event Messaging that facilitate intermodule communication and flexible triggering options over Ethernet, thereby eliminating overhead normally attributed to application software running on the host controller. The EX1402 supports easy integration and synchronization of multiple devices through the IEEE-1588 v2 Precision Time Protocol standard for synchronization, providing an architecture that can be scaled from 10s to 1000s of channels.

Multiple boxes can be easily distributed extremely close to the measurement points of interest reducing the run length of analog cable and minimizing errors induced by noisy environments. Additionally, Power Over Ethernet (PoE+) enables a single cable to be used for both power and data capture. All measurement data is returned with IEEE-1588 timestamp values with typical accuracies of <200nS ensuring that data is tightly correlated across the test article.

16-CHANNEL ISOLATED HIGH VOLTAGE MEASUREMENT INSTRUMENT **EX1402**



LXI – The Industry Standard for Ethernet Instrumentation

Created in 2004 and adopted by the test and measurement industry in 2005, LXI (LAN Extensions for Instrumentation) defines a core set of capabilities that ensure compliant devices interact consistently in an instrumentation network. As an LXI-certified device, the EX1402 provides the convenience of LAN communications and control with features such as an embedded web page for monitor and control and a consistent means of identification on the network. Connect the device directly to your network using industry-standard cables with the assurance that it will be a trusted and proven ‘network citizen.’

Isolated Measurements

Challenging measurement environments such as areas with a high level of electrical noise or where transient power surges can occur require unique protection capabilities in order to safeguard against common-mode noise or ground loop problems. The EX1402 provides exceptional input protection and isolation across a wide range of operating conditions, protecting the instrument from harmful voltages while ensuring measurement integrity. The Ethernet communications interface and input power are isolated from the analog front end inputs.

Self-Test

Manufacturing and test environments of today are dynamic, dictating minimal downtime of test systems in order to meet increasing product throughput demands. Ensuring that acquired data is reliable and instrument calibration can be turned around quickly are keys to the success of any production team. VTI embeds intelligence into the EX1402 to facilitate maximum system ‘uptime’ and increase manufacturing efficiency. Built-in self-test can be invoked under software control prior to each critical test. A simple pass-fail result will be returned after completing system health diagnostics, including temperature and voltage level measurements of the on-board processor and can be used to prevent a test from running in the event of a failure.

EX1402 16-CHANNEL ISOLATED HIGH VOLTAGE MEASUREMENT INSTRUMENT

1. Performance Specifications

All specifications are typical (stated at the 95% confidence interval at 23°C ±5°C) unless otherwise stated.

GENERAL SPECIFICATIONS	
Number of Channels	16 Isolated and fully differential inputs
Input Power Requirements	Input Voltage: 12V to 50V DC, must be isolated to 1500Vrms Power (AUX): 12.5 W typical, 15 W max 1PoE+ Power: 12.5 W typical, 15 W max
Channel Input Type	Voltage
Voltage Input Range	±420 V, ±10.0 V, ±1.0 V (Peak)
Input Overvoltage Protection	Up to ±450V peak between the two terminals of analog channel
Input Impedance	2 MΩ differential 1MΩ Single Ended
Input Coupling	DC only
Input Connector	3-pin Screw Terminal from TE connectivity.
Accuracy - Typical	± (% of reading + offset) 1V Range: ± [(0.03%+9PPM/°C)Rdng + 0.002%Rng + 2μV/°C] 10V Range: ± [(0.03%+10PPM/°C)Rdng + 0.002% Rng+ 5μV/°C] 420V Range: ± [(0.05%+25PPM/°C)Rdng + 0.002% Rng+ 66μV/°C]
Power Input Protection	±50V and reverse polarity
Fan Control Logic	Variable speed FAN controls for improved measurement accuracy/stability

Specifications subject to change without notice.

GENERAL SPECIFICATIONS

Isolation – Analog Inputs	Insulation, Compliant to EN 61010-1:2010/A1:2019 and IEC 61010-2-030:2021, Pollution degree II, Material IIIa, Altitude < 3000m, Over-voltage Category I, applicable for secondary circuits derived from the Mains Input Channel to Ground: ± 500 V Peak continuous working voltage Input Channel to Channel: ± 1000 V Peak continuous working voltage between channels
Common Mode Rejection Ratio (CMRR)	-100dB typical at 1KHz Signal
Channel To Channel Crosstalk	-115 dB Typical at 1kHz Signal
Total Harmonic Distortion (THD)	-85 dB Typical at 1kHz Signal
Supported Sampling Rate	Support Sample Rates: Programmable up to 128k SPS with filtered Decimation from 128k, 102.4k, 100k, 78.125k, 65.536k, 39.0625k SPS Accuracy: ± 100 PPM
Programmable Digital Filters	None (No Filter): Raw data High Performance (FIR): 1 to 16 number of /2 stages (Selectable & Customizable) Low Latency (CIC): /4 to /8192 (Selectable) Medium Latency (CIC+CFIR): Low latency CIC filter, followed by /4 FIR Filter (Customizable) Post Filter Blind Divider: 1 - 65536 (selectable)
Passband Ripple	$< \pm 0.005$ dB over the passband of $0.45 \times$ Sample Rate

Specifications subject to change without notice.

CLOCK AND TRIGGER SPECIFICATIONS

Electrical Specifications	Maximum Input Voltage: -0.5V to 5.5V, ESD protected Input Impedance: 50 Ohm series terminated with a 10k Ohm pulldown resistor Minimum Input Pulse Width: 1 μ s Minimum Output Pulse Width: 10 MHz $V_{IL} < 0.8V$ $V_{IH} > 3.5V$ $V_{OL} < 0.65V$ @ 32 mA $V_{OH} > 3V$ @ 32mA $I_{MAX} < 50mA$ max
---------------------------	---

Specifications subject to change without notice.

EX1402 16-CHANNEL ISOLATED HIGH VOLTAGE MEASUREMENT INSTRUMENT

DIO SPECIFICATIONS

Number of DIO Channels	8 Isolated Digital input and Output channels
Electrical Specifications	Maximum Input Voltage: -0.5V to 5.5V, ESD protected Input Impedance: Signal is pulled low by a 10k Ohm resistor Minimum Input Pulse Width: 100 μ s Minimum Output Pulse Width: 100 μ s, updated synchronously with the ADC sampling, prior to decimation $V_{IL} < 0.8V$ $V_{IH} > 2.0V$ $V_{OL} < 0.55V @ 10 \text{ mA}$ $V_{OH} > 2.0 V @ 10 \text{ mA}$ $I_{MAX} < 10\text{mA max per channel, 20mA max per bank}$
Connector	9 pin standard D-Sub Female socket

Specifications subject to change without notice.

USB 2.0: A USB 2.0 HOST CONTROLLER INTERFACE IS IMPLEMENTED

Speeds	USB full speed (480Mbps)
Connector	USB Type A

NETWORK / DATA PORT

Connection	10/100 Base-T (auto MDI-X)
Connector	RJ-45

ENVIRONMENTAL SPECIFICATIONS FOR EX1402

Operating Location	This module should be operated indoors in a controlled environment, protected from exposure to the elements (i.e. direct sunlight, precipitation, wind, etc.)
Input Connectors	Voltage: 3POS TERM BLOCK HDR 3POS Clock & Trigger: SMB
Dimensions	1.68" H x 8.69" W x 10.00" D (all dimensions are in inches)
Reliability	MTBF: > 225,000 hours Methodology: Telcordia (Bellcore) SR-332, Issue 3 Environment = GB, Quality Level = II, 25C ambient environment, 90% UCL
Weight	4.7 lbs (2.1 kg)
Temperature	Operating: 0 °C to +50 °C Storage: -40 °C to +80 °C
Humidity Operating	5% – 95% (non-condensing)
Altitude	Up to 3000 Meters
Shock and Vibration	Conforms to MIL-PRF-28800 Class 3
CE Compliance	EMC EN 61326 Class A, Criteria A
Creepage and Clearance Calculations	Pollution degree 2, Material IIIa (PCB), and an altitude up to 3000

Specifications subject to change without notice.

ORDERING INFORMATION

70-0691-000R	EX1402, 16-Channel Isolated High Voltage Measurement Instrument
56-0739-120R	EX14XX AC/DC Power Supply, 120W, PSE Certified
56-0739-000R	EX14XX AC/DC Power Supply 60W
70-0626-900R	EX14XX-RK001, Rack Mount Kit
41-0620-015R	EX14XX Rack Mount Filler Panel



9250 Brown Deer Road • San Diego, CA 92121 • USA
vti.sales@ametek.com • +1 858-450-0085

VTIinstruments.com