LXinstruments GmbH Rudolf-Diesel-Str. 36 71154 Nufringen Germany



TECHNICAL PRODUCT INFORMATION

Test & measurement instruments
high - quality
moderate prices
excellent precision

Your contact:

Technical support, services, demo & rental equipment, price information & quotes, consulting:

Tel.: +49(0)7032 / 895 93-3

- Mail: sales@lxinstruments.com
- Web: www.lxinstruments.com

Shop: www.lxinstruments.com/shop





WWW.POWERANDTEST.COM

EX1403A

16-CHANNEL STRAIN/BRIDGE, OHMS/RTD, VOLTS DIGITIZER



FEATURES

- 16-Channel Strain/Bridge, Ohms/RTD & Voltage Measurements
- 24-bit, delta-sigma ADC, simultaneous sampling
- Programmable Sample Rate up to 128kSPS
- Full, Half & Quarter Bridge with 120Ω , $350\Omega \& 1k\Omega$ bridge completion
- Voltage Excitation: 0.5V to 10V
- Current Excitation: 0.46mA
- 2-Wire & 4-Wire Ohms/RTD
- Bridge Zero Balancing
- Built-In-Self-Test (BIST)
- Strain Lead Wire Calibration
- Shunt Calibration: 50kΩ, 100kΩ & External provided by User
- TEDS Support
- LXI Ethernet Interface
- IEEE-1588 Synchronization
- Power over Ethernet (PoE) or 10–50 V DC input
- Built-in Parallel Data Streaming
- Full-featured Embedded Web Interface
- Compact 1U Half-rack Form Factor

Overview

The EX1403A Precision Bridge and Strain Gauge Instrument sets a new standard for strain and bridge measurements, delivering the highest performance measurements possible while controlling overall test hardware costs.

Sixteen channels of strain or voltage, independent 24-bit ADCs per channel, extensive software-selectable filtering, and independent signal conditioning paths deliver exceptional accuracy and reliability.

Built-in signal conditioning, programmable excitation, and selectable bridge completion, all integrated into the instrument and configurable on a per-channel basis, greatly simplify setup and configuration. With unmatched performance, accuracy and reliability, the EX1403A is the "go-to" solution for the most complex structural test applications worldwide.

A single system that can provide high-quality static or high-speed strain measurements:

- Airframe structural and fatigue test
- Rocket and satellite structural test
- Wind tunnel flight load test
- General purpose bridge measurements
- Load frame materials testing

Scalable for High-Speed Synchronized Data Acquisition

In addition to its core set of features, the EX1403A integrates Extended Functions as defined in the LXI specifications to provide box-to-box synchronization to correlate acquired data precisely. Time-stamping of data and LAN Event Messaging that simplify intermodule communication and flexible triggering options over Ethernet; this eliminates the overhead normally attributed to application software running on the host controller.

The EX1403A supports easy integration and synchronization of multiple devices through the IEEE-1588 v2 Precision Time Protocol standard for synchronization, providing an architecture that can be scaled from tens to thousands of channels. Multiple instruments can be easily distributed extremely close to the measurement points of interest, reducing the run length of analog cabling and minimizing errors induced by noisy environments.

Additionally, Power Over Ethernet (PoE) enables a single cable to be used for both power and data capture. All measurement data is returned with IEEE-1588 timestamp codes with typical accuracies of <200nS, ensuring that acquired data is tightly correlated across the test article.

Confidence

Manufacturing and test environments of today are dynamic, dictating minimal downtime of test systems in order to meet increasing product throughput demands. Ensuring that acquired data is reliable and that instrument calibration can be turned around quickly are keys to the success of any production team. VTI embeds intelligence into the EX1403A to facilitate maximum system "uptime" and increase manufacturing efficiency.

Built-In-Self-Test (BIST), Self-CAL, Lead-Wire CAL, or Shunt CAL can be executed prior to a critical test to have confidence that digitizer and connections to transducers are OK.



Connectivity

Created in 2004 and adopted by the test and measurement industry in 2005, LXI (LAN Extensions for Instrumentation) defines a core set of capabilities that ensure compliant devices interact consistently in an instrumentation network. As an LXI-certified device, the EX1403A provides the convenience of LAN communications and control with features such as an embedded web page for monitoring and control and a consistent means of identification on the network. Connect the device directly to your network using industry-standard cables with the assurance that it will be a trusted and proven "network citizen."

EX1403A 16-CHANNEL STRAIN/BRIDGE, OHMS/RTD, VOLTS DIGITIZER

Input Specifications	
Parameter	Specification
No. of Channels	16 channels
Input Connector	RJ45 connector (8 wire), pinout compatible with EX1629
Input Type	Differential
Input Range	Volts: ±10V, ±1V, ±0.1V Strain: ~±40kµε; Range=0.1V, Exc.=5V, GF=2 Ohms: 20kΩ, 2kΩ, 200Ω
Accuracy (Tcal±3°C)	Volts: 0.1V Range: ± ((0.10%+140PPM/°C) Rdng + 9μV + 1μV/°C 1V Range: ± ((0.10%+60PPM/°C) Rdng + 53μV + 5μV/°C 10V Range: ± ((0.10%+10PPM/°C) Rdng + 442μV + 50μV/°C Strain (Range=0.1V, VExc=5V, GF=2, 100SPS): ½ Bridge 120Ω: ± ((0.10%+140PPM/°C) Rdng + 15με +14με/°C ½ & ½ Bridge 350Ω & 1kΩ: ± ((0.10%+140PPM/°C) Rdng + 15με +6με/°C Full Bridge: ± ((0.10%+140PPM/°C) Rdng + 2με +0.5με/°C Note: excluding errors from lead wire resistance. Excitation to be applied to gage for >30min before zero balancing bridge (measure Vunstrained) 2/4Wire-Ohms & RTD(Ω): ± ((0.05%+140PPM/°C) Rdng +0.01% Rng)
Maximum Input, no damage	±12V. ESD protected to ±10kV
Input Ground Isolation	No channel to channel Ground Isolation
Input Coupling	DC
Input Impedance	>100 MΩ each input to ground
Slew Rate: 10% to 90% FS	30 V/µs Typical
Common Mode Rejection	-120dB Typical, <100 Hz -100dB Typical, 100Hz – 1kHz -90dB Typical, 1kHz – 10kHz
Channel-to-Channel Crosstalk	-120dB Typical, <1kHz: Overdriving 1 channel does not affect performance of other channels
Bridge Zero Balance	Software nulling: Excitation to be applied to strain gage for >30min before zero balancing bridge to ensure gage & completion resistors have thermally stabilized
Bridge Types	Full, Half (½), Quarter (¼)
Bridge Completion	 ½ Bridge Completion Software Selectable: OFF, 120Ω, 350Ω, 1000Ω 350Ω & 1kΩ: SMD Thin Film, 0.1% ±13 ppm/°C 120Ω: SMD Thin Film, 0.1% ±60 ppm/°C Bridge completion resistance measured within ±0.05% and stored in memory for use during internal shunt calibration ½ Bridge Completion: 10k-10k thin film resistor network, 0.1% ±25 ppm/°C

Self Calibration & Self-Test (BIST)				
Strain Shunt Calibration	Unit can shunt the strain gage RG or the internal $\frac{1}{2}$ bridge completion with either an internal 50k Ω or 100k Ω (12PPM/°C measured with 0.05% accuracy and stored in memory) or an external resistor connected on the front panel provided by the user. Unit can compute a gain correction factor that compensates for errors due to lead wire, excitation, internal gain errors, and temperature.			
Strain Lead Wire Calibration	Unit can measure lead wire resistance and verify connections to the gage are ok. The unit can compute a gain correction factor that compensates for errors due to lead wire.			
Built-In Self-Test (BIST)	Unit verifies that all internal critical voltages are within specified limits: power source (POE vs. AUX), power supply voltages, calibration reference voltages, excitation voltages, calibration date, internal PCB temperature, fan speed.			

VTI

AMETEK Programmable Power 9250 Brown Deer Road San Diego, CA 92121 +1 (858) 450-0085 www.powerandtest.com

4

RELIABLE DATA FIRST TIME EVERY TIME

Excitation Specifications				
Channel-to-Channel Isolation	All channels share the same ground. Each channel provides separate excitation circuitry			
Voltage Excitation	Software Selectable per channel: +0.5V, +1V, +2V, +5V, +10V with Sense lines Measured with ±0.05% accuracy and saved in memory to convert voltage to strain units ±10 ppm/°C for +5V & +10V; ±30 ppm/°C for +0.5V, +1V & +2V; ±50ppm/year Current Limit: 35mA Load regulation: <0.05% for load change < 32mA Crosstalk: <0.03% effect on other channels from load changes Noise: 20 µVRMS Typical, 50kHz bandwidth Excitation Sensing: Max. Voltage at ±P: 11V Voltage Excitation Monitoring: every ~1 second when all 16 channels enabled for dynamic excitation			
Current Excitation	EX1403A: 0.46mA Stability: ± 230 ppm/°C ± 50 ppm/year Measured with $\pm 0.05\%$ accuracy and saved in memory to convert voltage to ohms units Compliance Voltage: >10V; Output Impedance: >10M Ω			
Excitation Protection	Protected if driven by external voltage source: -0.3V to +12V Crosstalk: A short does not affect Excitation accuracy in other channels ± 10 kV ESD protection			

Analog-to Digital Converter (ADC)				
ADC	24-bit, delta-sigma ($\Delta\Sigma$) simultaneous sampling			
ADC Data Rate (SPS) (fDATA)	Programmable up to 128kSPS with filtered Decimation from 128k, 102.4k, 100k, 78.125k, 65.536k, 64k, 51.2k, 50k, 39.0625k, 32.768k & 19.53125k SPS. Additional up to 65536 unfiltered (blind) decimation Accuracy: ±100PPM			
ADC Digital Filter Passband (±0.05% ripple)	0.417 * f _{DATA}			
ADC -3dB Bandwidth	0.424 * <i>f</i> data			
Group Delay	39 / <i>f</i> DATA			
Settling Time (Latency)	78 / f _{DATA}			

TEDS (Transducer Electronic Data Sheet)		
Protocol	MicroLAN	
Baud Rate	9600 Baud (default)	
Electrical Specifications	5V	
Driver type	Maxim Integrated DS2480B	
Capacitance Loading (1-Wire input)	<2000pF	

Engineering Units (EU) Conversion

Unit can convert raw ADC counts to Engineering Units (EU): Volts, Ohms (Ω), Strain (ε). Linearization formulas are used for ¼ bridge and Half/Full bridge with Poisson effect. User can provide linear scaling factors (gain & offset) to convert to EU any other transducer type, i.e. volts to pressure or force, Ohms to temperature °C or °F



AMETEK Programmable Power 9250 Brown Deer Road San Diego, CA 92121 +1 (858) 450-0085 www.powerandtest.com

RELIABLE DATA FIRST TIME EVERY TIME

Software and Drivers

Puilt in CUI			_						_			- NULUSIAN.
BUIII-IN GUI	Soft Front Panel ©										Soft Front Panel @	Plot Type Draw Points
available via	EX1403 - 235627										EX1403 - 235627	Poll Current Value Table 👻 🖸
	Phil Data 🔒										Def Data	Time: 5948.036768259
a standard	Measurement	Channel Confe	guration ®								Measurement	0.0000032 CH14: 3.26480 µr
	Stain Setup	Enabled	Function	Range	Offset	Mode	Record Size	Transducer Conversion	Auto Cal	Current Value	Channels	0.0000
Web Browser.	Advanced Strain Setup	ALL 🖬	Stain	• •	0.0 Auto Zers	Offerendal N	9124	[0.1]	Auto Cal		Stain Setup	Section 1
	00	CHI 🖬	Strain	v 1V v	0.0 Auto Zerr	Differential >	9124	[0,1]	Auto Cal		Advanced Deals Setup	0.0000028
	Sampling	CHS C	Seain	4) (129) -4	0.0 Auto Zerr	Citterondal N	9324	[0.1]	Auto Cal		DID	0.000025
	Advanced Tabs	CH0	Stain	* 100eV*	0.0 Auto Zero	Offerendad >	1024	[0.1]	Auto Cal		Sampling	- CH14
	Storage Devices	сна 🖬	Stain	♥ 100mV ♥	0.0 Auto Zerr	Collevendial *	9024	[0.1]	Auto Cal		T Advanced Tabs	The second water water
	Sync & Time	CH6 🖸	Stain	✓ 100eV ✓	0.0 Auto Zerr	Offerendal N	1124	[0.1]	Auto Cal			
	Trigger Sources	CH6 🖬	Seain	✓ 100eV ✓	0.0 Auto Zerr	Offerential •	1124	[0.1]	Auto Cal			0.000002
	Arm Sources	CHP 🖸	Seale	* 100erV *	C.O Auto Zerr	Offerendal *	9024	[0.1]	Auto Cal			0.000011
	Events	CHB E	Resistance	✓ 13k0 ✓	0.0 Auto Zero	Offerendal 1	9124	[0.1]	Auto Cal			4,600 4,600 5,000 5,200 5,400 5,600 5,600
	Alarms	сна 🖬	Resistance	· 10010 ·	C 0 Auto Zerr	Ciferential	9124	[0.1]	Auto Cal			Seconds (+1)
	Overhead	CHIIO C	Resistance	· 1000 ·	C.0 Auto Zerr	Differential N	1024	[0.1]	Auto Cal			CVT Polling Frequency (ms) Maximum CVT Points
	TEDS	CHI1 C	Stain	< 100eV v	C.0 Auto Zerr	Differential *	9124	0.1	Auto Cal			512
	Configuration	CHI2 C	Sevin	· NORV ·	0.0 Auto Zen	Cifferential •	9024	[0,1]	Auto Cal			Advanced Strain Setup ()
Full Calibration	Full Calibration	creas C	Desin	- HODAY -	C.0 Auto Zerr	Concentral S	1024	0.1	Auto Cal			Unstrained Voltage Gauge Factor Poisson Ratio Other Gauge Resistance Lead Wire Resistance Shunt Cal Gala
	Calibration References	CH14 C	Votage	V HOURY V	100 Auto Zen	Considerated of	1 1124	0.1	Auto Cal	_		ALL Measure 2.0 0.3 (350.0 0.0 Measure) Measure
	Self Test	Child E	Votage		CO References	Otherstel a	1 1014	0.1	Auto Cal			CH14 0 1032653003 Measure 2 0 8 3 (360 0 Measure) 1 01149661924 Measure
	1.00	Cuild C	and the		No Inco Serie	Control of	- Inter	124.1	(And Cal)	I		

Driver support for operation in Windows, Linux, MATLAB and LabVIEW.



EXIab Turnkey Solution

- Easy to use spreadsheet configuration
- Flexible real-time data displays
- Data can be viewed and exported in a number of data formats
- Provides extended features such as "snapshot," calculated channels and Rosette support, event handling and alarms
- Multiple configurations and options







AMETEK Programmable Power 9250 Brown Deer Road San Diego, CA 92121 +1 (858) 450-0085 www.powerandtest.com

Trigger Input/Output Specifications			
Trigger Input	Maximum Input Voltage: -0.5V to 5V, ESD protected VIL: < 0.5V; VIH: > 2.5V		
Trigger Input Impedance	Signal is pulled high by a 4.7k Ohm resistor		
Minimum Trigger Input Pulse Width Detection	lµs		
Trigger Output Swing	0V to 5V		
Output Pulse Width for trigger event	lμs		
Output Drive	Can drive 50 Ohm coax. Source series termination for 50 Ohms		

Clock Input/Output Specifications				
Output Swing	0V to 3V			
Duty Cycle	40% to 60%			
Frequency	10 MHz phase locked to the ADC sample rate			
Enable/Disable	Software control			

Network / Data Port	
Connection	10/100 Base-T (auto MDI-X)
Connector	RJ-45
USB Interface	USB 2.0 high speed (480Mbps)
Connector	USB type A

Power	
POE+	IEEE 802.3at
Auxiliary Power	+12VDC to +50VDC The auxiliary power source supplies the power even if PoE power is already present. The unit may reboot if auxiliary power is applied after it had already been powered from a POE+ compliant PSE
Max. Input Power Requirements	25 Watt (includes 5W maximum to bridge transducer)
Power Input Protection	Reverse polarity protection
Power Input Protection Power Control	Reverse polarity protection The unit can identify if the unit is operating from a POE+ type 2 PSE or from AUX power, and whether power is good.



AMETEK Programmable Power 9250 Brown Deer Road San Diego, CA 92121 +1 (858) 450-0085 www.powerandtest.com

EX1403A 16-CHANNEL STRAIN/BRIDGE, OHMS/RTD, VOLTS DIGITIZER

Environmental	
Temperature	Operating Temperature: 0°C to +50°C Storage Temperature: -40°C to +80°C MIL-PRF-28800 Class 3
Relative Humidity, non-condensing	Operating: 10%-90% Storage: 5% to 95% MIL-PRF-28800 Class 3
Vibration & Shock	MIL-PRF-28800 Class 3
Altitude	4600M, MIL-PRF-28800 Class 3
CE Compliance	YES
MTBF	200k Operational Hours
Service Life	> 10 Years

Physical	
Dimensions	Half Rack 1U: 8.70" x 1.68" x 9.81"; 220.6mm x 42.7mm x 249.2mm
Weight	6.6 Lbs or 3kg
Material	Steel
Color	Powder Coating Black Texture Semi-Gloss

Ordering Information	
Model	Description
70-0655-100R	EX1403A, 16-Channel Strain/Bridge, Ohms/RTD Digitizer
56-0739-120R	EX14XX AC/DC Power Supply, 120W, PSE Certified
56-0739-000R	EX14XX AC/DC Power Supply 60W
70-0626-900R	EX14XX-RK001, Rack Mount Kit
41-0620-015R	EX14XX Rack Mount Filler Panel



AMETEK Programmable Power 9250 Brown Deer Road San Diego, CA 92121 +1 (858) 450-0085 www.powerandtest.com

RELIABLE DATA FIRST TIME EVERY TIME