

LXinstruments GmbH
Rudolf-Diesel-Str. 36
71154 Nufringen
Germany



TECHNICAL PRODUCT INFORMATION

Test & measurement instruments

- ▶ high - quality
- ▶ moderate prices
- ▶ excellent precision

Your contact:

Technical support, services, demo & rental equipment, price information
& quotes, consulting:

Tel.: +49(0)7032 / 895 93-3

Mail: sales@lxinstruments.com

Web: www.lxinstruments.com


Shop: www.lxinstruments.com/shop

Programmable DC Electronic Load

E5000 Series




Kewell E5000 Series is a compact, high-power DC electronic load featuring wide operating range and high dynamic frequency. With basic and composite modes and varied load functions, the E5000 series is widely applicable to load testing for traction battery, fuel cell, DC charging pile, OBC, SMPS, UPS, PV module, etc.



6.6kW in 4U

Ultra-high power density



$\geq 42\text{A}/\mu\text{s}$

Rapid current slew rate




3 current ranges

Precise current measurement



25kHz

Dynamic current/resistance loading



Sine Wave of 20kHz

Supporting analysis of fuel cell impedance




50kHz

Dynamic load sweep function with gradient of 0.01Hz



Composite Modes

CVCC / CRCC / CVCR / AUTO



Parallel


Flexible paralleling for higher power

KEWELL TECHNOLOGY CO., LTD.

<https://www.kewelltest.com/>

sales2@kewell.com.cn

(QR code) >>





Normal
Fundamental, Cost-effective



Pro
Fully-featured, Multi-scenario



E5000 Series					
Function Params		Version		Normal	Pro
Voltage	0-150V	0-600V	0-1200V	●	●
Power (kW) / Current(A)	2.2/200	2.2/140	2.2/80	●	●
	4.4/400	4.4/280	4.4/160	●	●
	6.6/600	6.6/420	6.6/240	●	●
	13.2/1200	13.2/840	13.2/480	●	●
	19.8/1800	19.8/1260	19.8/720	●	●
	26.4/2000	26.4/1680	26.4/960	●	●
Functions	Basic modes (CC/CV/CR/CP)			●	●
	Dynamic current load (CCD)			●	●
	Battery discharge			●	●
	Short-circuit simulation			●	●
	Von/Voff			●	●
	Vpk+/-			●	●
	LIST mode			●	●
	Dynamic resistance load (CRD)			-	●
	Composite modes (CVCC/CRCC/CVCR/AUTO)			-	●
	Sine wave mode (SWD)			-	●
	Dynamic load sweep (SWP)			-	●
	Determination of OCP/OPP points			-	●
Rated values*1	Voltage accuracy			0.05%+0.025%F.S.	0.025%+0.025%F.S.
	Current accuracy			≤0.1%+0.1%F.S.	0.05%+0.05%F.S.
	Power accuracy			≤0.2%+0.3%F.S.	≤0.2%+0.2%F.S.
	Current slew rate			0.5mA/μs-0.6A/μs 2mA/μs-3A/μs 5mA/μs-6A/μs	0.5mA/μs ~ 6A/μs 2mA/μs ~ 21A/μs 5mA/μs ~ 42A/μs
	Dynamic current loading frequency			10kHz	25kHz
	Min. operating voltage			1.8V@600A	
Input parameters	Grid voltage			100 ~ 240Vac	
	Grid frequency			47-63Hz	
General parameters	Operating temperature			0 ~ 40℃	
	Dimensions			665(D)*445(W)*178(H)	

Note: ● come with standard equipment - none / *1: taking E5000-6K6-0150-0600 for example

